
## Future Kaon Physics at Fermilab

How we're **Still** going to measure  $K^+ \rightarrow \pi^+ \nu \nu$ 



### Peter S. Cooper, Fermilab May 13, 2004

- I. Recent history.
- II. Physics goals and situation.
- III. A new technique and its challenges
- IV. Our immediate plans
- V. Future Kaon Physics at Fermilab

BNL May 13, 2004

# CKM Status and how to proceed




- o CKM(E921) at Fermilab is an approved experiment to measure Br[ K+ $\rightarrow \pi$ +  $\nu$  n ] with 100 signal / <10 background in a high flux separated kaon beam at 22 GeV/c
- o P5 stops CKM Oct 2003


P5 judged CKM to be an elegant world class experiment which based on present budgetary models should not proceed.

- Adapt to an unseparated ~45 GeV/c beam in KTeV hall P940
  - Demonstration of μMegas in NA48 ® tracking in 230MHz tractable
  - Other 3 trackers unchanged (2 RICHes + Straws in vacuum)
  - Vetoing photons gets easier ( $E_{\pi^0} > 1 \text{ GeV } \otimes > 7 \text{ GeV}$ )
  - Accidental backgrounds?


# Primary Physics Goal: Precision Measurement of Br[ $K^+ \rightarrow \pi^+ \nu \bar{\nu}$ ]




This decay is determined by loop processes to high order in the SM, and hence has a reach for *new* physics at the EW scale and beyond.



The SM rate can be reliably calculated; hence any deviation in the measured rate is a signal for new physics.



# Measuring $|V_{td}|$ with $K^+ \rightarrow \pi^+ \nu \overline{\nu}$



### o K<sup>+</sup> $\rightarrow \pi^+ \nu \bar{\nu}$ is the best way to measure $|V_{td}|$ in the Standard Model

- Structure of K<sup>+</sup> controlled by measurement, NO final state interactions.
- Theoretical uncertainties are small (m<sub>charm</sub>) and robustly estimated. (~8%)
- Need 100 signal events with <10 background (6%) to match theory error.

#### o Experimental Challenge

- Br[ $K^+ \rightarrow \pi^+ \nu \overline{\nu}$ ] = (8±1) x 10<sup>-11</sup> (Standard Model)
- 3 clean events seen in BNL787 /949 (Br =  $15^{+13}_{-9}$  x  $10^{-11}$ )

#### o The tyranny of tiny decay rates

- •100 events /  $10^{-10}$  (Br) / 1% (acc) =  $10^{14}$  K decays must be studied
- •10<sup>7</sup> sec/year  $\rightarrow$  10<sup>7</sup> K decay /sec to see 100 in 1 year
- Need to control background to 10<sup>-11</sup> of all K<sup>+</sup> decays

# Challenging the Standard Model of CP Violation



S

Consider the Quartet of "Golden Mode" measurements:


$$\sin(2\beta)$$
,  $K^0 \rightarrow \pi^0 \ \nu \overline{\nu}$ ,  $K^+ \rightarrow \pi^+ \ \nu \overline{\nu}$ ,

 $\Delta m_d / \Delta m_s$  in  $B_d^0$  and  $B_s^0$  Decays




#### $\Gamma(\pi \nu \nu) = 2xSM$


#### expected sensitivities



CKM Fitter Results, D. Jaffe (BNL).

# Hasn't B physics done it all already?





Who will measure orthogonal to  $\sin 2\beta$ ? Bs/Bd mixing CDF /D0 / BTeV /LHCb But  $\xi(\Delta m_s/\Delta m_d) = 1.15 \pm 0.05^{+0.12}_{-0.00}$ ?  $1.25 \pm 0.10$ 

 $B_s$ ?  $D_sK$  BTeV / LHCb  $K^+ \rightarrow \pi^+ \nu \overline{\nu}$  P940

#### •hep-ph/0312259

 $B \rightarrow \pi\pi$ , New Physics in  $B \rightarrow \pi K$  and Implications for Rare K and B Decays

Andrzej J. Burss,\* Robert Fleischer,\* Stefan Rocksiegel\* and Felix Schwab\*\*

Physik Department, Technische Universität Minchen, D-88748 Gerching, Germany
 Theory Division, CERN, CB-1211 Geneva 23, Spitzerland
 Max-Planck-Institut für Physik – Wester-Beisenberg-Institut, D-80808 Minish, Germany


#### Abstract

The measured  $B\to \pi\pi_\pi\pi^K$  branching ratios adultst paraling patterns. We point out that the  $B\to \pi\pi$  intentity can be useful assumed start in the Standard Model (SM) through non-factorizable backeter interference effects, whereas the  $B\to \pi K$  system may indicate new physics (NP) in the electroweak (EW) perguin sector. Using the  $B\to \pi\pi$  data and the SU(3) theore symmetry, we may fix the inchesions:  $B\to \pi K$  parameters, which allows us to show that any currently observed feature of the  $B\to \pi K$  system can be easily explained through enhanced EW programs with a large CPe infanting SP phase. Restricting correction in a pre-fix accentre, when NP outcomed through  $B^*$  programs, we describe that in care K and B decays, where an enhancement of the  $K_+ \to \pi^+ \pi^+$  ratio by one order of magnitude, with BR( $K_- \to \pi^+ \pi^+ \pi^-$ )  $> B2(K^* \to \pi^+ \pi^+)$ ,  $B1(K_- \to \pi^+ \pi^+ \pi^-) = C(10^{-10})$ ,  $(8\pi \pi^0)^{1/2} = 0$ , and a large ferward-backward CD asymmetry in  $B_+ \to K^+ \pi^+ \pi^-$ , are the most spectratular effects. We address also other rate K and B decays,  $\pi^+$  is and  $B_+ \to K^- \pi^-$ , are the most spectratular effects. We address also other rate K and B decays,  $\pi^+$  and  $B_+ \to K^- \pi^-$ .


- •hep-ph/0311353 Lepton flavor mixing and K® pn`n decays, Y. Grossman, G. Isidori, H. Murayama
- •hep-ph/0112135  $K^{+}$   $p^{+}$  n n a rising star on the stage of flavor physics, G. D'Ambrosio, G. Isidori •many more

# New Physics sensitivity in

$$K^+ \rightarrow \pi^+ \nu \overline{\nu}$$




#### New CP violating physics



 $K^0 \rightarrow \pi^0 \nu \overline{\nu}$ 

Sensitive to only CP violating  $s \rightarrow d$  new physics

# Other Physics Measurements




#### o $\pi^+$ decay physics

- $\Gamma[\pi^+ \to e^+ \nu(\gamma)] / \Gamma[\pi^+ \to \mu^+ \nu(\gamma)]$  is calculated to 0.05% in the SM
- Helicity suppresses the dominant V-A and IB amplitudes
- $\pi^+ \rightarrow e^+ v \gamma$  Dalitz plot access to non V-A terms in hadronic weak current
- An excellent place to search for models like leptoquarks, multiple Higg, etc.

#### o Other K<sup>+</sup> decay physics

- All the other K decays studies from the CKM proposal remain
  - $K_{e3}$ ,  $K_{e4}$ ,  $K_{\mu 3}$ ,  $K_{\mu 4}$ ,  $K^{+} \rightarrow \pi^{+} e^{+} e^{-}$ ,  $K^{+} \rightarrow \pi^{+} \mu^{+} \mu^{-}$
  - Lepton flavor violation  $K^+ \rightarrow \pi^- \mu^+ \mu^+$ , etc.
  - T odd correlations in  $K^+ \rightarrow \pi^+ l^+ \nu \gamma$
- $\Gamma[K^+ \rightarrow e^+ \nu(\gamma)] / \Gamma[K^+ \rightarrow \mu^+ \nu(\gamma)], K^+ \rightarrow e^+ \nu \gamma$  in parallel with pion decays


# Changes in the physics situation



#### What's changed since the CKM approval in 2001?

- o Another  $K^+ \rightarrow \pi^+ \nu \nu$  event from BNL E949.
- o B<sub>s</sub> mixing isn't going to be measured at the SM level (17 ps<sup>-1</sup>) soon.
- o Some unusual CP violation results are emerging at Belle
  - e.g.  $B^0 \to \phi K_S^0$  asymmetries disagrees with  $\psi K_S^0$  (&  $K^+K^-K_S^0$ ,  $\eta' K_S^0$ )
- o Lack of 1st row unitarity ( $\sim 2.5\sigma$ ) and new measurements of  $V_{us}$  topical
- o There is experimental evidence for non V-A terms in the pion hadronic weak current in  $\pi^+ \to e^+ \nu \gamma$ 
  - 5 $\sigma$  claim by PiBeta for tensor form-factor  $F_T/F_V = -0.061 \pm 0.011$  hep-ex/0311013, hep-ex/0312029
  - ISTRA at IHEP also reported a non-zero tensor form-factor. Phys.Lett.**B243** (1990)308, hep-ph/0307166

# Experimental Technique




- O High Flux Un-separated 37-53 GeV/c Beam 4% K<sup>+</sup>
  - Proton /  $\pi^+$ : 120 / 100, 230 MHz total, 1x1 cm<sup>2</sup>, 0.1x0.1 mRad<sup>2</sup>
  - 10 MHz K<sup>+</sup>, 1.7 MHz decay in the acceptance.
  - 5 x10<sup>12</sup> 120 GeV proton/sec in slow spill from the Main Injector to produce the required K<sup>+</sup> beam (17% of design intensity)
  - Debunched proton beam required (~10% 53MHz ripple ok).

#### Apparatus


- Decay in flight spectrometer with both velocity (RICH) and momentum (magnetic) spectrometer both both  $K^+$  and  $\pi^+$ .
- Significant requirements on photon vetoes
- All detector technologies used are well established
- Redundancy is critical to measure all backgrounds
- Exploit signal regions on both sides of  $K^+ \to \pi^+\pi^0$ .


## **Apparatus**




- o Decay in flight
- o Redundant high rate detectors and veto systems.
- o separated K+ beam at 22 GeV/c.


Un-separated + beam at 37-53 GeV





## NA48 KABES data







# Ring Imaging Cherenkov Counters


C K M

- High rate high resolution
- Matched to momentum resolution
- O Based on successful Selex RICH
- Photo-detectors are individual PMTs







# Simulated Spectrometer Performance




- Missing mass resolution for  $M^2_{\pi^0}$ from  $K^+ \to \pi^+ \pi^0$
- Matched resolution from momentum and velocity spectrometers
- Low non-Gaussian tails
- Uncorrelated measurements
   Backgrounds from Mis-measurements to be studied and quantified from the data
- Study needs to be redone for P940



## Acceptance



- o Acceptance was re-evaluated. Decay fraction increased  $13\% \rightarrow 16.5\%$
- o PNN2 acceptance limited to 1.4x PNN1 pending more serious background studies
- o Nearly identical sensitivity as CKM for same 120 GeV beam incident.



parameter	CKM	E921	
$K^+flux[MHz]$	30	10	
beam-sec/year	$0.75 \times 10^{7}$	$0.75 \times 10^{7}$	
years of data	2	2	
sensitive K decays	$5.8 \times 10^{13}$	$2.5\times10^{13}$	
nominal Branching ratio	$1 \times 10^{-10}$	$1 \times 10^{-10}$	
taxes (other losses)	-15%	-15%	
PNN1 (s+b)	$95 + \le 10$	$44 + \le 4$	
PNN2	$(130+ \le 40)$	$62+ \le 20$	
total	$95+ \le 10$	$106+\leq 24$	
Br precision	< 11%	< 12%	

## **Backgrounds Remaining**



## **Background Source**

## Effective BR (x10<sup>-12</sup>)

•	$K^+$ -	$\rightarrow$	$\mu^{\scriptscriptstyle +}$	$\nu_{\mu}$
---	---------	---------------	------------------------------	-------------

• 
$$K^+ \rightarrow \pi^+ \pi^0$$

$$\bullet \quad K^{\scriptscriptstyle +} \to \mu^{\scriptscriptstyle +} \; \nu_{\mu} \; \gamma$$

• 
$$K^+ A \rightarrow XK^0 \rightarrow \pi^+ e^- V$$

• 
$$K^+A \rightarrow \pi^+X$$
 (trackers)

• 
$$K^+A \rightarrow \pi^+X$$
 (gas)

**CKM** 

$$\frac{0.51}{<10.6}$$

# Our plan




- o We are in the middle of this redesign now we need to:
  - Complete the unseparated beamline design for NM2
  - Assess KABES feasibility in a 230 MHz beam
  - Re-evaluate backgrounds from Kaon interaction in detectors
  - Estimate backgrounds from non-kaon interaction accidentals
  - Evaluate PNN2 cuts, acceptance and backgrounds
  - Re-assess losses from deadtime, reconstruction, ...

#### o Our Plan


- Complete the list above
- Have external technical review of the redesign (a-la CKM)
- Return to Fermilab and the PAC with a vetted re-design
- Time scale of months

# Future Kaon Physics at Fermilab




- o Fermilab is planning a Proton Driver to increase fluxes by ~10x
  - Both an 8 GeV SCRF proton Linac and an 8/16 GeV high flux conventional synchrotron are under consideration.
  - Physics goals include sensitivity neutrino experiments, ...
  - •Time frame is the next decade (~2015)
- o High Sensitivity Kaon physics is a natural for this machine but
  - The Main Injector was sold on the same promise in ~1989
  - Save the KTeV 1999 run no kaon physics will be done in the first decade of main-injector operation
- o If Fermilab and US-HEP aren't interested in a kaon physics program for today discussing one in a decade is fatuous.


## Extra Slides



### **Proton Economics**

- o We require debunched protons from the Main Injector (10% 53MHz ripple is OK).
- o Separate fast (neutrino+Pbar) and slow spill Main Injector cycles make these different modes of operation independent by timesharing
- o N=8 fast cycles / slow cycle gives both fast and slow spill 2/3 of the maximum available to either.
- o Setting N in this model is a program planning decision.






o The Particle Physics Project Prioritization Panel (P5) reviewed BTeV, CKM and the Tevatron detector upgrades; concluding for CKM:

Evaluation – The subpanel was impressed with the excellent work of the proponents on the design of the experiment and their successful prototyping results. CKM is an elegant world-class experiment, which would be able to produce important physics results. However, the committee assigns it a lower priority than the BTeV experiment. The main reason is that BTeV has a much broader physics program at a comparable cost.

Suggestions Based on Prioritization – The present Fermilab plan calls for a similar funding profile and time-line for BTeV and CKM construction, with both starting to take data around 2009. The P5 Subpanel believes that this plan is likely to be too ambitious given the need to optimize the physics from the Tevatron Collider, as well as the desire to have BTeV completed promptly. Based on current budgetary models, P5 does not recommend proceeding with CKM.

## Changes to the apparatus



o Beamline

- existing NM2 beamline and NM3-4 detector hall (KTeV)
- 120 GeV proton transport estimated at 250K\$+50% (C. Brown)
- Target station can be modified designed for required intensity
- o Kaon RICH
- $10 \rightarrow 12$ m, radiator gas to H<sub>2</sub> at 1.1 atm only sees beam Kaons


o DMS

- same strawtube in vacuum design as CKM, hole for 10cm beampipe
- o Pion RICH
  - Same basic design as CKM (1atm Ne, 3000 1/2in PMTs)
  - Optics modified to accommodate beampipe down the middle.
- o Photon Vetoes
  - 90% of photons now hit CsI 1- $\varepsilon$  ~ 3x10<sup>-6</sup> for E>1 GeV
  - VVS 5 existing Pb-scint rings from KTeV + 9 new ones of CKM design
  - Photon energy threshold can be >1.5 MIP everywhere.
- o Muon Vetoes
- combined KTeV MVS + descoped CKM design

o UMS

replace CKM MWPC's with  $\mu Megas$  of KABES design

### P940 Collaboration



- o Groups from 4 national laboratories and 5 universities.
- o 44 people including 6 postdocs + students
- o Roots in KTeV, Selex, HyperCP, CDF, BNL787/E949, BNL871, IHEP-Istra, -Lepton, -Sphinx
- o Substantial experience in rare and ultra rare kaon decay experiments
- o Collaboration will double with time.

  The technical review should help with this.

#### Charged Kaons at the Main Injector

June 6, 2002

A Proposal for a Precision Measurement of the Decay  $K^+ \to \pi^+ \nu \bar{\nu}$  and Other Rare  $K^+$  Processes at Fermilab Using the Main Injector

J. Frank, S. Kettell, R. Strand Brookhaven National Laboratory, Upten, NY, USA

L. Bellantoni, R. Coleman, P.S. Cooper\*, T. R. Kobilarcik, H. Nguyen, E. Ramberg, R. S. Tschirhart, H. B. White, J. Y. Wu Fermi National Accelerator Laboratory, Batavia, IL, USA

G. Britvich, V. Burtowoy, A. V. Inyakin, V. Kurshetsov, A. Kushnirenko, L. G. Landsherg, V. Molchanov, V. Obraztsov, S. I. Petrenko, V. I. Rykalin, A. Soldatov, M. M. Shapkin, O. G. Tchikilev, D. Vavilov, O. Yushchenko Institute of High Energy Physics, Serpukhov, Russia.

> V. Bolotov, S. Laptev, A. Polarush, A. Pastsiak, R. Sirodeev Institute of Nuclear Boscarch, Troisk, Bussia

> J. Engelfried, A. Morelos Instituto de Fisica, Universidad Autonoma de San Luis Potosi, Mexico

A. R. Barker, H. Huang, R. Niclasen, M. Wilking University of Colorado, Boulder, Colorado, 80309

M. Campbell, R. Gustafson, M. Longo, H. Park University of Michigan, Ann Arbor, Michigan 48109

C.M. Jenkins

University of South Alabama, Mobile, Alabama 36688

K. Lang

University of Texas at Austin, Austin, Texas 78712

C. Dukes, L. Lu, K. Nelson University of Virgina, Charlottesville, Virgina 22901

\* Spokesman: P.S. Cooper, pcooper@fnal.gov, (630) 840-2629 Web Address: www.fnal.gov/projects/ckm/Welcome.html

### What do we need



- o A reaffirmation that Fermilab is still committed to the world class P940 physics program.
- Near term support from Fermilab to complete the redesign and review.
  - Fermilab technical support
    - main need is for beam-line design and cost
    - engineering design
    - cost estimation
  - Support for Russian visitors
  - Travel support to interact with NA48
  - Support for the technical review committee
- o The collaboration, particularly the university groups, need support and encouragement in order to persevere.

# Straws in Vacuum: Old Wine, New Bottle.


- Mechanical properties extensively studied. (Fermi-Pub 02-241-E)
- Prototype operating in vacuum.
- Proven Principle. Now ready for detailed engineering.



# Photon Veto Inefficiency and Technology


u C K t **(Mar)** 

- o 0.3% VVS Prototype built
- o Tested at JLAB in an e<sup>-</sup> beam
- o Achieved  $<1 \times 10^{-5}$  ( $3 \times 10^{-6}$ ) veto inefficiency at 1 GeV (required  $3 \times 10^{-5}$ )





# KABES µMEGAS from NA48



V.Kekelidze

# New elements for NA48/2 Beam Spectrometer KABES (TPC micromegas)

